

## FLATSCREEN

Flat panelled screen providing a flush finish to hide equipment, ductwork, and pipework.



## DESIGN

- Configurable in increment sizes in height and length to suit your requirements.
- Flush finish panel with colour matched top channel and screen posts.
- Screen area 8.5 kg/m<sup>2</sup> (not including added acoustic elements)
- Heights available in 100mm increments
- All aluminium components with stainless steel fixings – backed by a 20 year warranty.
- Peacemaker acoustic panels can be added to provide an effective sound absorber to the internal face.
- Provides a complete visual block.
- A1 fire rated / powder coated items A2 fire rated

## APPLICATION

- Available on all Configured Platforms screen systems.
- Provides a visual screen.

## VERSATILE

- Polyester powder coated to RAL or BS colour ranges.
- Special finishes on request.
- Configurable in 600mm increment lengths to suit your requirements.
- The lightweight aluminium design makes it easy for carrying, craning and assembly.

## INSTALLATION

- Kit form allows assembly by general installer trade with our easy to follow installation manual.
- Take advantage of our approved installer network to obtain the most efficient install.

## SPECIFICATION REQUIREMENTS

- Provide Configured Platforms Flatscreen to elevations where aesthetically required to screen off equipment, ductwork, and pipework.
- Complies to BS EN 516 2006 and BS EN 1090-3 2008
- Backed by a 20 year product warranty.

A1 fire rated/  
A2 fire rated




Rw26dB

## OPTIONAL ACCESS GAP OR GATE

- An access gap of any 600mm increment wide is configurable in the Flatscreen.
- A Self Closing Access Door 600mm wide is configurable in the Flatscreen.
- A Self Closing Double Access Door 1200mm wide (2 x 600mm doors) is configurable in the Flatscreen.

## SECTION DETAIL



Acoustic Performance (Rw26dB)

63	125	250	500	1000	2000	4000	Hz
11.8	17.5	19	22.1	23.4	29.1	23.8	dB

